



# **PLT-M1503 Three Phase SmartMe- ter Powerline Tester**

## **Datasheet**

## **Main features**

- Simultaneous three phase measurement and testing of physical level of PLC communication. The device supports measurement of only one phase or any 2-phase combination.
- designed for G3-PLC, CELENEC-S-FSK or PRIME communication technology (within Cenelec A-band) and FCC band performing spectral analysis in either 20kHz-110kHz, 20kHz-500kHz (option) or 20kHz-50MHz broadband (option) frequency bands
- a web browser is used for data monitoring and data logging operations which runs on a PC or any mobile device
- time based roll-oscilloscope analysis (option) available for much easier immediate transmit/receive PLC signal recognition
- data logging made inside the device through a triggering mechanism either on-demand or based on a timer
- data logs done in csv or animated gif format at configurable time intervals either on-board as data logger (no supervision required) or as in-browser downloading for further off-line data analysis
- remote operation via LTE modem enabling operation from the office
- used for specific outdoor and high voltage environment
- solid construction and design with ABS plastic enclosure in robust rubber or textile casing
- power related issues:
  - 230V AC LINE input voltage, power supply included
  - Embedded rechargeable Li-Ion battery
  - Up to 4h standalone battery operation
- communication capabilities:
  - WiFi operating in access point mode
  - LTE USB modem option enabling remote device access from the office - via a self-established VPN connection (modem can be provided)

## **Device Application**

The Three Phase PowerLine Tester PLT-M1503 represents the diagnostic instrumental equipment in the form of a spectrum analyzer and/or oscilloscope enabling the observation of communication signal levels through measuring PLC signal communication directly on-site where the problem has been detected. PLT-M1503 is a key part of the comprehensive power line solution solving concept which enables a 100% successful daily energy meter readout rate. The PLT-M1503 is predominately intended to be used by utility companies dealing with PLC smart meter deployments. It is a well-known fact at utility companies that PLC communication which is used for transferring predominately energy readout data once per month (but also other power quality related data if necessary) is many times subject to either interference or impedance related disturbances in the 20-100kHz or 20-500kHz frequency ranges.

Through the OpenVPN server one or multiple PLT devices can be directly managed remotely via LTE or ethernet TCP/IP connection. Through an automatic VPN connection, the PLT-M1503 can be accessed through a web browser on any mobile or static device.

It is therefore crucial for the utility company to have an effective system in place which can remove these disturbances. The PLT-M1503 offers all the necessary means to any utility company dealing with PLC meter rollouts to observe the communication issues at the physical level by performing spectral analysis as well as time based oscilloscope monitoring in the

20kHz-110kHz/500kHz frequency bands. This enables their specialists to find out the reason that is causing the undesired disturbances in a very economic manner.

## **Device full functionality**

- One, two or three phase measurement and testing of physical level of PLC communication
- designed for G3-PLC, CELENEC-S-FSK or PRIME communication technology (within Cenelec A-band) and FCC band performing spectral analysis in either 20kHz-110kHz or 20kHz-500kHz (option) frequency bands
- A web browser used for data monitoring and data logging operations on a PC or any iOS or Android mobile device
- Online viewing of recorded data files through an integrated slider-based viewer and online browsing, deleting, and downloading of recorded data
- PC-based "Offline PLT Viewer" SW for analyzing recorded data is included with the device enabling 3D heatmap analysis and animated gif creation of multiple records at the same time
- Time based roll-oscilloscope signal analysis available for much easier immediate transmit/receive PLC signal recognition
- Remote operation via LTE modem (option) enabling operation from the office through a secure VPN tunnel
- Data recorder logging is implemented either on-board the device or at the server side either on-demand, amplitude/frequency trigger-based or timer based
- Data recording is done on an 8GB or (optionally) 32GB flash memory which is enough for over 400 thousand (8GB) or 1.5 million (32GB) stored spectrum frames
- used for specific outdoor and high voltage (up to 250VAC) environment
- solid construction and design with ABS plastic enclosure in robust rubber
- Simple (button-less) on-site usage (connect & go)
- Solid manufacturing and safe use in all demanding environments (CAT IV compliance for TS measurements)
- dimensions: 29cm x 20cm x 6cm
- power related issues:
  - 230V AC LINE input voltage, power supply included
  - Embedded rechargeable Li-Ion battery
  - Up to 4h standalone battery operation
- communication capabilities:
  - WiFi operating in access point mode
  - LTE USB modem option enabling remote device access from the office - via a self-established VPN connection (modem can be provided)
- Interface
  - USB-A port (USB OTG)
  - Ethernet 1Gb/s

### **System components:**

- FPGA signal processor-based architecture with the following accessible interfaces:
  - 1 USB port (USB OTG) which is used for either WiFi dongle or LTE modem
  - Ethernet 1Gb/s – RJ-45 connector
- Galvanic decoupling and 20kHz-110kHz/500kHz bandpass filter unit (inside the device)
- Li-Po battery pack with 10Ah capacity (allows up to 4-hour operation)
- Measurement connection slots at front of device
- Four 2m Measurement cables
- Four 4mm connectors of type PJP CAT IV-300V compatible for any kind of probe attachment

- Three MC type 4 mm fused (6A) test clips with steel jaws and 1 non-fused neutral 4 mm test clip with steel jaws
- ON/OFF switch with LED indicator
- 4 LED battery charge indicator with button

## Compliance with standards

The PLT-M1501 unit complies with the following international standards:


Standard EN	Description
EN 61010-1:2010	<i>Safety requirements for electrical equipment for measurement, control, and laboratory use. General requirements</i>
CAT IV 300 compatible	<i>Device is suitable for origin of installation or utility level measurements on primary over-current protection devices and on ripple control units</i>

Declaration of conformity:

MEASUREMENT INPUT
Input: CAT IV 300V
Input impedance: 31 – 482 Ohm
Frequency: 50, 60 Hz (measured 10 – 500kHz)
Connection type: phase-to-neutral



MAINS POWER SUPPLY
Input: 100-240VAC, 50-60Hz
Output: 3.6-6.5VDC, min. 1.2A
Maximum rated power: 20W



## Ordering information

To order this product please use the following product ordering code:

PLT M1503-[freq]-[   X   ]

[freq] Frequency range: 110 or 500

- [O] Roll Oscilloscope for time domain
- [L] LTE USB modem with prepaid SIM
- [M] 32GB Memory card (8GB is included)
- [PS] External Power Supply